



DATASHEET

304306

Arendo Mizu Retro Kettle With Temperature Settings

TECHNICAL INFORMATION

BASIC INFORMATION

| | |
|--------------------------|--|
| Dimensions | H (26.5 cm) x W (22.5 cm) x L (20 cm) |
| Weight (kettle) | • 732 g |
| Weight (basis) | • 410 g |
| Material | ABS / stainless steel |
| Colour | Grey |
| Scope of delivery | <ul style="list-style-type: none"> • Arendo Mizu Retro Kettle With Temperature Settings • Base with integrated connection cable • User manual |

DETAILED DESCRIPTION

| | |
|-----------------------------|--|
| Capacity | Max. 0.5l |
| Socket Controller | Strix |
| Power Supply | 220-240V AC, 50/60 Hz |
| Power consumption | 800 - 1000 W |
| Cable length | Aprox. 68 cm |
| Plug | Type F CEE 7/7 |
| Temperature levels | • 40°C • 50°C • 60°C • 70°C • 80°C • 90°C • 100°C |
| LED display | white LED display for temperature selection / keep warm / power |
| Temperature settings | 4 Basic sensor probes (Temp Select, Keep Warm, Boil, ON/OFF) |
| Standby consumption | <0,5W |
| Protection | Dry-running protection, overheat protection, automatic shut-off |
| Features | <ul style="list-style-type: none"> • Keep warm function for 30 minutes • 360 degree base station • Buzzer (1x when pressing a key / 5x after completion) • Concealed stainless steel heating element • Automatic switch-off • Signal tone at start and end can be switched off |

| | |
|----------------|---|
| GS Mark | ✓ |
|----------------|---|



DATENBLATT

304306

Arendo Mizu Retro-Wasserkocher mit Temperatureinstellung

TECHNISCHE INFORMATIONEN

BASIS-INFORMATIONEN

| | |
|-------------------------------|---|
| Abmessungen | H (26,5 cm) x B (22,5 cm) x L (20 cm) |
| Gewicht (Wasserkocher) | • 732 g |
| Gewicht (Basiseinheit) | • 410 g |
| Material | ABS / Edelstahl |
| Farbe | Grau |
| Lieferumfang | <ul style="list-style-type: none"> • Arendo Mizu Retro-Wasserkocher mit Temperatureinstellung • Basisstation mit integrierter Kabelaufwicklung • Bedienungsanleitung |

DETAILLIERTE SPEZIFIKATIONEN

| | |
|---------------------------------------|---|
| Kapazität | Max. 0,5 l |
| Controller-Typ | Strix |
| Netzspannung | 220-240V AC, 50/60 Hz |
| Stromverbrauch | 800 W - 1000 W |
| Kabel-Länge | Ca. 68 cm |
| Steckertyp | Typ F CEE 7/7 |
| Temperaturstufen | • 40°C • 50°C • 60°C • 70°C • 80°C • 90°C • 100°C |
| LED-Anzeige | weiße LED-Anzeige für Temperaturwahl / Warmhalten / Power |
| Wählbare Temperatureinstellung | 4 Sensortasten in der Basis (Temp Select, Keep Warm; Boil, ON/OFF) |
| Standby-Verbrauch | <0,5W |
| Sicherheitsstandard | Trockengehschutz, Überhitzungsschutz, Automatische Abschaltung |
| Eigenschaften | <ul style="list-style-type: none"> • Warmhaltefunktion für 30 Minuten • 360-Grad-Basisstation • Summer (1x beim Drücken einer Taste / 5x nach Beendigung) • Verdecktes Edelstahl Heizelement • Automatische Abschaltung • Signalton beim Start und bei der Beendigung abschaltbar |
| GS-Siegel | ✓ |